



# Safety Data Sheet

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** LENI TEXTURE PASTE ( 98250TEP)  
**Supplier:** Boyle Industries Pty Ltd  
8 Redland Drive Mitcham 3132 Victoria Australia  
TEL: +03 9874 2266 FAX: +03 9874 2880

## 2. COMPOSITION INFORMATION

Component	CAS No.	Concentration(%)
Distilled water	7732-18-5	19.90
716P Polymer Emulsion	30795-23-4/7732-18-5	43.40
Propylene glycol	57-55-6	5.70
AMP-95	124-68-5/7732-18-5	0.10
ACTICIDE LA1209	26172-55-4	0.06
ACTICIDE L	52-51-7	0.04
Silicon dioxide	7631-86-9	5.70
Barium sulfate precipitated	7727-43-7	15.00
Texanol(TM) Ester Alcohol	25265-77-4	1.00
ACRYSOL ASE-60 thickener	25212-88-8/7732-18-5	2.60
R-902+ titanium dioxide	13463-67-7	6.50

## 3. HAZARDS IDENTIFICATION

### Primary Routes of Exposure

**Inhalation**  
**Skin Contact**  
**Eye Contact**

### Inhalation

Inhalation of vapour or mist can cause the following:  
Irritation of nose and throat

### Eye Contact

Direct contact with material can cause the following:  
Slight irritation

### Skin Contact

Prolonged or repeated skin contact can cause the following:  
Slight irritation

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air.

**Skin Contact:** Wash with water and soap as a precaution. If skin irritation persists, call a physician.

**Eye Contact:** Rinse with plenty of water. If eye irritation persists, consult a specialist.

**Ingestion:** Drink 1 or 2 glasses of water. Consult a physician if necessary. Never give anything by mouth to an unconscious person.



## 5. FIRE-FIGHTING MEASURES

---

**Thermal decomposition:** Thermal decomposition may yield acrylic monomers.

**Suitable extinguishing media:** Use extinguishing media appropriate for surrounding fire.

**Specific hazards during fire-fighting:**

Material can splatter above 100°C/212F. Dried product can burn.

**Special protective equipment for fire-fighters:**

Wear self-contained breathing apparatus and protective suit.

## 6. ACCIDENTAL RELEASE MEASURES

---

### Personal precautions

Use personal protective equipment.

Keep people away from and upwind of spill/leak.

Material can create slippery conditions.

### Environmental precautions

CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

### Methods for cleaning up

Contain spills immediately with inert materials (e.g., sand, earth).

Transfer liquids and solid diking material to a separate suitable container.

## 7. HANDLING AND STORAGE

---

### Handling

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed.

Do not breathe vapours, mist or gas.

**Further information on storage condition:** Keep from freezing-product stability may be affected.

**STIR WELL BEFORE USE.**

### Storage

**Storage temperature:** 1-49°C

**Other data:** Monomer vapours can be evolved when material is heated during processing operations.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Exposure controls

**Eye protection:** safety glasses with side-shields eye protection worn must be compatible with respiratory protection system employed.

**Hand protection:** The gloves listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Neoprene gloves.

**Respiratory protection:** Use certified respiratory protection equipment meeting EU requirements (89/656/EEC), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by



boyle industries

technical means of collective protection or by measures, methods or procedures of work organization.

**Protective measures:**

Facilities storing or utilizing this material should be equipped with an eyewash facility.

**Engineering measures:** Use only in area provided with appropriate exhaust ventilation.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

Physical state	Ointment
Odour	Ammonia
pH	9.0-10.0
Boiling point/range	100°C
Melting point/range	0°C water
Flash-point	Non-combustible
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Vapour pressure	2,266.474 Pa at 20°C water
Relative vapour density	<1.0 water
Water solubility	Dilutable
Relative density	1.00-1.20
Viscosity, dynamic	50-400mPa.s
Evaporation rate	<1 water
Percent Volatility	49-51% water

**NOTE:** The physical data presented above are typical values and should not be construed as a specification.

**10. STABILITY AND REACTIVITY**

---

Hazardous reactions	None known. Stable.
Materials to avoid	There are no known materials which are incompatible with this product.
Polymerization	Product will not undergo polymerization.

**11. TOXICOLOGICAL INFORMATION**

---

No-toxic

**12. ECOLOGICAL INFORMATION**

---

There is no data available for this product.



## 13. DISPOSAL CONSIDERATIONS

---

**Environmental precautions:** CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water

**Disposal:**

Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. For disposal, incinerate or landfill at a permitted facility in accordance with local, state and federal regulations.

## 14. TRANSPORT INFORMATION

---

**Classification for Road and Rail transport:**

Not regulated (Not dangerous for transport)

**Classification for SEA transport (IMO-IMDG):**

Not regulated (Not dangerous for transport)

**Classification for AIR transport (IATA/ICAO):**

Not regulated (Not dangerous for transport)

**Hazchem Code**

None Allocated

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations.

## 15. REGULATORY INFORMATION

---

Labelling in accordance with EC Directives.

Hazard warning labelling not compulsory.

## 16. OTHER INFORMATION

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered and may not be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.